

SAFETY DATA SHEET



SECTION 1 – IDENTIFICATION AND COMPANY DETAIL

Product Name: C-10 / 250A Electrolyte
Product Code(s): Monode C-10, LectroEtch 250A
Recommended Use: For use in the Electro-Chemical Etching Process
Manufacturers Name: Monode Marking Products, Inc.
Address: 9200 Tyler Boulevard
Mentor, OH 44060

Emergency Telephone: (440) 975-8802, available during offices hours,
8:00am – 5:00pm EST, Monday – Friday, in English.

Fax Number: (440) 975-8836
Date Prepared: 31 March 2015

HMIS	
H	2
F	0
R	1
PPE [†]	
[†] Sec. 8	

SECTION 2 – HAZARDS IDENTIFICATION



Hazardous Pictogram:

Signal Word: **WARNING**

Precautionary Statement: Harmful if swallowed.
Do not swallow.
Avoid Skin and Eye contact.

Inhalation: N/A

Ingestion: Large quantities of Oxalic Acid can be fatal. It can possibly damage G.I. tract and central nervous systems. Nausea, shock, convulsion, facial discoloration and death at five grams

Skin contact: Generally aggravated by exposure: Dermatitis may possibly be aggravated on contact

Eye contact: Irritation, burning to mucous membranes on contact

SECTION 3 – COMPOSITION / INFORMATION ON INGREDIENTS

Not considered Hazardous under current OSHA Regulations.

Hazardous Components (specific chemical identity/ Common name):

SOLIDS:	Nitrate Salt (trade secret)	4%
	Oxalic Acid (trade secret)	0.1%

LIQUIDS:

TRADE SECRET: The specific chemical identity and/or exact percentage (concentration) of composition has been withheld as a trade secret.

SAFETY DATA SHEET



SECTION 4 – FIRST AID MEASURES

Skin contact: Wash with soap and water thoroughly after handling.
Eye contact: Flush eyes with thoroughly with water for 15 minutes; if irritation continues, consult physician.
Ingestion: Do not induce vomiting. Give diluted milk of magnesia, lime water, or milk.
Inhalation: Local exhaust is sufficient.

Always seek medical attention if irritation continues.

SECTION 5 – FIRE-FIGHTING MEASURES

Suitable extinguishing media: N/A
Special fire fighting procedures: N/A
Unusual fire and explosions hazards: None

SECTION 6 – ACCIDENTAL RELEASE MEASURES

Personal Protective Equipment: rubber gloves, safety goggles, optional-apron

Steps to be taken in the event of accidental release:

Small Spills: Flush with water to sewer.

Large Spills: Use suitable absorbent and dispose of in DOT approved waste containers.

SECTION 7 – PRECAUTIONS FOR SAFE HANDLING AND USE

Steps to be taken in the event of spillage or chemical release:

Small Spills: Flush with water to sewer. Minimize release of chemicals into the environment.

Large Spills: Use suitable absorbent and dispose of in DOT approved waste containers.

Waste disposal method: Disposal of material should be in compliance with all current local, state and federal regulations.

Precautions to be taken in Handling and Storage: Keep container tightly closed. Keep from freezing (32 degrees [F]) Wash hand thoroughly after handling. No eating, drinking or smoking in work area.

Incompatibility: (materials to avoid) Strong acids, strong reducing agents, chlorites, and hypochlorites.

Hazardous Polymerization: May Occur

Other Precautions: Wash hands thoroughly after handling.

SECTION 8 – EXPOSURE CONTROLS – PERSONAL PROTECTION

Occupation Exposure Limits: N/A



SAFETY DATA SHEET

Personal Protective Equipment:

Respiratory System:	Local exhaust is sufficient.
Skin and Body:	Optional-Apron
Hands:	Rubber gloves.
Eyes:	Safety glasses or goggles
Other/Special:	Local exhaust is sufficient.

SECTION 9 – PHYSICAL AND CHEMICAL PROPERTIES

Physical State:	Liquid and suspension.
Color:	Clear fluid.
Odor:	slight odor
Odor Threshold:	N/A
pH:	1.8 to 2.2
Boiling Point:	212° (F)
Melting/Freezing Point:	N/A - Freezing below 32° (F)
% Volatile:	N/A
Flash Point:	N/A
Fire Hazards in presence of various substances:	N/A
Auto-ignition temperature:	N/A
Explosive Properties:	No risk
Lower explosion limit:	N/A
Oxidizing properties:	N/A
Vapor Pressure:	(mm Hg.) @ 25° (C) [77° (F)] : 23.7
Evaporation Rate:	Like water
Density:	Like water
Solubility:	Complete (100%)
Vapor Density:	Like water

SECTION 10 – REACTIVITY DATA

Stability:	STABLE
Conditions to avoid:	N/A
Incompatibility: (materials to avoid)	Strong acids, strong reducing agents, chlorites, and hypochlorites.
Hazardous Decomposition or By-products:	None, but surrounding fire may release oxides of nitrogen.
Hazardous polymerization:	Will not occur.

SECTION 11 – TOXICOLOGICAL INFORMATION

Carcinogenicity:	NTP: No	IARC Monographs: No	OSHA Regulated: No
-------------------------	---------	---------------------	--------------------

The toxicological information for the components is: N/A

Acute effects

Causes eye irritation.

Causes skin irritation.

Material is irritating to mucous membranes.

May be harmful by ingestion or if contacted with skin. Large quantities of Oxalic Acid can be fatal. It can possibly damage G.I. tract and central nervous systems. Nausea, shock, convulsion, facial discoloration and death at five grams.



SAFETY DATA SHEET

SECTION 12 – ECOLOGICAL INFORMATION

Potential as Pollutant: Material is not considered a pollutant.

SECTION 13 – DISPOSAL CONSIDERATIONS

Effective waste disposal treatment should be utilized. COD – 495,000ppm

Biological: Capable of biological oxidation

SECTION 14 – TRANSPORT INFORMATION

Special Precautions: Keep container tightly closed. Keep from freezing (32 degrees [F]).

This is a Non-Hazardous product.

UN Number

US DOT (United States Department of Transportation): Not Regulated

IMO/IMDG (International Maritime Dangerous Goods): Not Regulated

IATA (International Air Transport Association): Not Regulated

ADR (Agreement on Dangerous Goods by Road (Europe)): Not Regulated

RID (Regulations Concerning The International Transport of Dangerous Goods (Europe)): Not Regulated

AND (European Agreement Concerning The Carriage of dangerous Goods by Inland Waterways): Not Regulated

SECTION 15 – TRANSPORT INFORMATION

Safety Phrases: N/A

Risk Phrases: N/A

Regulations: N/A

SECTION 16 – OTHER INFORMATION

**Source of key data used to
Compile Safety Data Sheet:**

Material Safety Data Sheet. Essentially similar to U.S. Department of
Labor Form OSHA-20

Issue Date: 26 Feb 1987

Changes to Issue: 14 June 2024

WE CANNOT ANTICIPATE ALL CONDITIONS UNDER WHICH THIS INFORMATION AND OUR PRODUCTS, OR THE PRODUCTS OF OTHER MANUFACTURERS IN COMBINATION WITH OUR PRODUCTS MAY BE USED. WE ACCEPT NO RESPONSIBILITY FOR RESULTS OBTAINED BY THE APPLICATIONS OF THIS INFORMATION OR THE SAFETY AND SUITABILITY OF OUR PRODUCTS, EITHER ALONE OR IN COMBINATION WITH OTHER PRODUCTS. USERS ARE ADVISED TO MAKE THEIR OWN TESTS TO DETERMINE THE SAFETY AND SUITABILITY OF EACH SUCH PRODUCT OR PRODUCT COMBINATION FOR THEIR OWN PURPOSES. UNLESS OTHERWISE AGREED IN WRITING, WE SELL THE PRODUCTS WITHOUT WARRANTY, AND BUYERS AND USERS ASSUME ALL RESPONSIBILITY AND LIABILITY FOR LOSS OR DAMAGE ARISING FROM THE HANDLING AND USE OF OUR PRODUCTS, WHETHER USED ALONE OR IN COMBINATION WITH OTHER PRODUCTS.

THE FORMULAS USED FOR THESE PRODUCTS ARE CONSIDERED CONFIDENTIAL TRADE SECRETS. THIS INFORMATION IS FOR OUR CUSTOMERS EYES ONLY.

MONODE COMPLIES WITH ALL APPLICABLE RULES AND REGULATIONS UNDER THE TSCA. (TOXIC SUBSTANCES CONTROL ACT)

© MONODE MARKING PRODUCTS, INC.